



Super Glue 1409 (Gel)

I. MANUFACTURER: SUR-LOK CORPORATION
WALWORTH, WISCONSIN, USA 53147
EMERGENCY TELEPHONE: 1-888-784-7711

DATE PREPARED: October 24, 2017

II. HAZARDOUS COMPONENTS: NONE

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TOXIC SUBSTANCE CONTROL ACT (TSCA) INVENTORY OF CHEMICAL SUBSTANCES MAINTAINED BY THE U.S. ENVIRONMENTAL PROTECTION AGENCY.

III. PHYSICAL / CHEMICAL CHARACTERISTICS:

Boiling Point: <300° F
Specific Gravity: 1.05
Vapor Pressure (mm Hg) <5 @ 30° F
Melting Point: N/A
Vapor Density (Air= 1) N/A
Evaporation Rate: N/A
Solubility in Water: Polymerized by water
Appearance /Odor: Transparent liquid with ester-like odor.

IV. FIRE AND EXPLOSION HAZARD DATA:

Flash Point (Method Used): T.C.C. 176° F Flammable Limits: N/A
Extinguishing Media: CO₂, Foam, Dry Chemicals
Special Fire Fighting Procedures: Fire can produce dense smoke containing hazardous products of combustion (see Section V), which may be a hazard to health. Self-contained breathing apparatus and procedures for fighting chemical fires should be employed.

V. REACTIVITY DATA:

Unstable. Avoid high temperatures, high humidity, and materials such as water, alcohols, amines and alkalis which may cause polymerization which may be exothermic.

Super Glue 1409 (Continued)

VI. HEALTH HAZARD DATA:

Possible routes of entry include skin and ingestion.

This product is not included on any list for carcinogenicity.

WARNING: Eye irritant. Bonds skin in seconds. Contains cyanoacrylate ester. This adhesive gives a virtually immediate, strong bond: apply only to surfaces to be bonded. Do not get adhesive on your skin or other parts of your body, or that of others. In case of body contact, flush with water. Seek medical attention for any eye or internal contact.

LIQUID EFFECTS:

EYE CONTACT: Cyanoacrylate adhesives are eye irritants and tissue bonders. Therefore, care, including the use of goggles, should be taken to prevent eye contact. In the event of eye contact, the eyes should be copiously flushed with water and medical aid sought immediately. If eyelids are bonded closed, only a qualified physician should attempt to separate them. In case of bonding corneal surface, forced separation is not recommended. Allow the eye to remain closed and the bond to separate naturally, which generally will occur within a few days.

SKIN CONTACT: Cyanoacrylate adhesives, while relatively non-toxic, are mild irritants to the skin. The Acute Dermal LD50 is >2000 mg/kg. However, strong bonds will quickly form between adjacent skin surfaces, e.g. fingers. These may be separated relatively easily by soaking the bonded area in warm, soapy water for several minutes and then gently peeling the bond. Alternatively, a dull instrument such as a thin wire or a table knife can be forced through the bond. With appropriate caution, solvents such as acetone or nail polish remover can be used effectively.

When skin contact is over a large area, the area should be flushed with large amounts of water. A soaking wet cloth can be used to wipe off excess adhesive. If the adhesive has soaked through clothing, flush the involved area with water. If the cloth has bonded to the skin, the removal of the bonded clothing without these precautions might result in skin damage. Cured adhesive will flake from the skin within a day or so or can be removed by treatment or by soaking with hot, soapy water.

ORAL CONTACT: Cyanoacrylates are relatively non-toxic materials (Acute Oral LD50 >5000 mg/kg). However, rapid polymerization (hardening) of the adhesive will take place in contact with the surfaces of the mouth. The mouth should be flushed copiously with water and medical aid should be sought immediately. Lips, if bonded, can be gently peeled apart, preferably with the aid of hot water or solvent.

Super Glue 1409 (Continued)

VAPOR EFFECTS:

EYES: Alkyl cyanoacrylate vapors are lachrymatory (tear producing) and can cause eye irritation and tearing in poorly ventilated areas.

MUCOUS MEMBRANES: Mucous surfaces can become irritated by prolonged exposure to cyanoacrylate vapors in poorly ventilated areas. Vapor irritation to the eyes and mucous membranes will be most noticeable under conditions of low relative humidity.

VAPOR CONTROL RECOMMENDATIONS:

- * Use adequate ventilation. Remove adhesive vapors with suitable exhaust ducting. Since cyanoacrylate vapors are heavier than air, place exhaust intake below work area. Activated charcoal filters using an acidic charcoal have been found effective in removing vapors from effluent air.
- * Avoid use of excess adhesive. Excess adhesive outside of bond area will increase level of vapors.
- * Assemble parts as quickly as possible. Long open times will increase level of vapors.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE:

Health hazard rating is 2, slightly hazardous. Fire hazard is 2, Flash point above 100 ° F not exceeding 200. Reactivity rating is 1, Unstable if heated.

Provide adequate ventilation in area of usage. When possible this should be achieved by the use of local exhaust ventilation and good general ventilation. Vapors are heavier than air, therefore, downward ventilation should be used. When handling cyanoacrylate adhesives, goggles or safety glasses should always be worn. Polyethylene gloves should be used to protect the hands. CAUTION: Do not use rubber or cloth gloves. Rubber gloves will bond when brought in contact with the adhesive and porous cotton gloves will absorb the adhesive and bond the gloves to the skin.

Store in original container below 40° F for prolonged shelf life.

In the event of small spills, material may be wiped up with a soaking wet cloth and the area cleaned with solvent. When large quantities of cyanoacrylate adhesive are accidentally spilled, the area should be flooded with water which will cause the liquid cyanoacrylate to cure. The cured material can then be scraped from the surface. It may then be incinerated observing all State, Federal and local anti-pollution and waste disposal regulations.

VIII. CONTROL MEASURES:

Transport: This product is not regulated for shipping purposes.

Other: Respiratory protection is not normally necessary unless product is used in enclosed area of poor ventilation or individual has a history of chronic respiratory disease. Local exhaust is recommended. Protective gloves are recommended during use (See section VII above). Always wash hands thoroughly after use.

The information on this data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.